





Průmyslové switche BDCOM zajišťují spolehlivou komunikaci v oblastech, kde jsou kladeny vysoké nároky na spolehlivost a redundanci, jako například smart city, energetika, doprava a další. Společnost BDCOM je již přes 30 let významným světovým dodavatelem širokého portfolia síťových produktů.




- Cenově dostupné průmyslové switche
- Teplotní odolnost -40 až 85°C
- Half-rack/Din-rail provedení
- EMC Třída 4
- Přepětová ochrana 6kV




L2 100M/1G Unmanaged Industrial Switches (DIN-RAIL)





				
Typ	IES200-1006T	IES200-LSTW1108	IES200-LSTW1140	IES200-LSTW2080
Main ports	6x 100M RJ-45	8x 100M RJ-45	5x 100/1000M RJ-45	8x 100/1000M RJ-45
Uplink	-	1x GE SFP ; 1x GE RJ-45	1x GE SFP	2x GE SFP
Features	Redundant power input Operating temp: -40~85°C Lightning protection 6kV	Redundant power input Operating temp: -40~75°C Lightning protection 6kV	Redundant power input Operating temp: -40~75°C Lightning protection 6kV	Redundant power input Operating temp: -40~75°C Lightning protection 6kV
PoE	-	-	-	-
Power Supply	DC (12~55V)	DC (12~55V)	DC (12~55V)	DC (12~55V)

L2 100M/1G Unmanaged Industrial PoE Switches (DIN-RAIL)





			
Typ	IES200-LSTW1108P	IES200-LSTW1140P	IES200-LSTW2080P
Main ports	8x 100M RJ-45	4x 100/1000M RJ-45	8x 100/1000M RJ-45
Uplink	1x GE SFP ; 1x GE RJ-45	1x GE SFP ; 1x GE RJ-45	2x GE SFP
Features	Redundant power input Operating temp: -40~75°C Lightning protection 6kV	Redundant power input Operating temp: -40~75°C Lightning protection 6kV	Redundant power input Operating temp: -40~75°C Lightning protection 6kV
PoE	PoE+	PoE+	PoE+
Power Supply	DC (48~55V)	DC (48~55V)	DC (48~55V)






L2+ 100M/1G Managed Industrial Switches (DIN-RAIL)

				
Typ	IES200-L25-2S4T	IES200-L25-2S8T / 4S8T	IES200-L25-2S4P	IES200-L25-2S8P / 4S8P
Main ports	4x 100/1000M RJ-45	8x 100/1000M RJ-45	4x 100/1000M RJ-45	8x 100/1000M RJ-45
Uplink	2x GE SFP	2x GE SFP / 4x GE SFP	2x GE SFP	2x GE SFP / 4x GE SFP
Features	Redundant power input Operating temp: -40~75°C Lightning protection 6kV	Redundant power input Operating temp: -40~75°C Lightning protection 6kV	Redundant power input Operating temp: -40~75°C Lightning protection 6kV	Redundant power input Operating temp: -40~75°C Lightning protection 6kV
PoE	-	-	PoE+ (120W)	PoE+ (240W)
Power Supply	DC (12~55V)	DC (12~55V)	DC (48~55V)	DC (48~55V)

L2+ 100M/1G Managed Industrial Switches (DIN-RAIL / Half-Rack)

				
Typ	IES2000-TU8S8T	IES2000-TU12S4T	IES2000-TW8S8P	IES2000-TU16T4S4X
Main ports	8x 100/1000M RJ-45	4x 100/1000M RJ-45	8x 100/1000M RJ-45	16x 100/1000M RJ-45 + 4x GE SFP
Uplink	8x GE SFP	12x GE SFP	8x GE SFP	4x SFP+
Features	Redundant power input AC/DC Operating temp: -40~85°C Lightning protection 6kV	Redundant power input AC/DC Operating temp: -40~85°C Lightning protection 6kV	Redundant power input Operating temp: -40~75°C Lightning protection 6kV	Redundant power input AC/DC Operating temp: -40~85°C Ring protection Stacking - BVSS Virtual Switching System - až 16
PoE	-	-	PoE+ (240W)	-
Power Supply	AC/DC hybrid input	AC/DC hybrid input	DC (12~55V)	AC/DC hybrid input

L3 lite Stackable Managed Industrial Switches (Rack-mounted)

			
Typ	IES2000-5024T4S	IES2000-5024T8C4X	IES2000-5024S8C4X
Main ports	24x 100/1000M RJ-45	16x 100/1000M RJ-45 + 8x RJ45/SFP Combo	16x 100/1000M RJ-45 + 8x RJ45/SFP Combo
Uplink	4x GE SFP	4x SFP+	4x SFP+
Stacking	BVSS Virtual Switching Systém - až 16	BVSS Virtual Switching Systém - až 16	BVSS Virtual Switching Systém - až 16
Features	Redundant power input AC/DC Operating temp: -40~85°C Ring protection	Redundant power input AC/DC Operating temp: -40~85°C Ring protection	Redundant power input AC/DC Operating temp: -40~85°C Ring protection
PoE	-	-	-
Power Supply	2x AC	2x AC	2x AC

Autorizovaný distributor pro ČR a SR

PROFcomms s.r.o. nabízí k produktům BDCOM přidanou hodnotu:

- technická podpora dálková nebo u zákazníka
- technická a produktová školení
- návrhy sítí a zápůjčky produktů

Kontakt

David Matula

Product & Sales manager

mobil: +420 736 625 791

E-mail: matula@proficomms.cz