



Aktivní síťové prvky Edge-Core

Edge-Core nabízí spolehlivé aktivní síťové prvky na technicky vysoké úrovni s výborným poměrem cena/výkon. Aktivní prvky Edge-Core jsou ideální volbou pro kancelářské a podnikové aplikace, serverovny, datová centra, ISP poskytovatele a Telco operátory. Rozsáhlé portfolio obsahuje L2/4 přepínače a L3 směrovače s managementem, aktivní prvky pro aplikace FTTx a bezdrátové Wi-Fi sítě.

Služby Next Business Day Shipment k jednotkám Edge-Core

- platí pro ČR a SR
- držení náhradní jednotky pro případ HW poruchy u zákazníka
- v případě nahlášení poruchy do 12:00 hod, je jednotka odeslána tentýž den
- lze zakoupit na 1,2,3,4 nebo 5 let od data zakoupení
- službu lze předprodávat dalším subjektům




ECView PRO Management

- výkonná SW aplikace s uživatelsky jednoduchým grafickým rozhraním
- správa síťových prvků firmy Edge-Core, ale i SNMP zařízení jiných výrobců




- **TECHNICKÁ PODPORA**
- **NÁVRH ŘEŠENÍ**
- **FINANCOVÁNÍ**
- **ŠKOLENÍ**
- **ZÁPŮJČKY**
- **SLA SLUŽBY**



L2 Unmanaged/Web Managed Gigabit Ethernet Switches for Enterprise




			
	Unmanaged	Unmanaged	Web managed
Typ	ECS1020-16T/24T	ECS1020-10P/16P	ECS2020-10T/10P/28T/28P
Main ports	16x/24x 10/100/100T	9x/16x 10/100/100T	8x/24x 10/100/100T
Uplink	-	1x GE SFP 100/1000 (10P)	2x/4x GE SFP
Stacking	-	-	-
Features	VLAN mode (ECS1020-16T) přepěťová ochrana 4KV	přepěťová ochrana 6KV	L2, IPv6, Web Only Management
PoE	-	PoE+ (max. 140/300W)	PoE+ (max. 70W/190W)
Power Supply	AC, podpora EEE (úspora až 65%)	AC, podpora EEE (úspora až 69%)	AC





L2 Smart Managed Gigabit Ethernet Switches for Enterprise / Small ISP

			
Typ	ECS2100-10T/10P/PE	ECS2100-28T/28P/28PP	ECS2100-52T
Main ports	8x 10/100/1000T	24x 10/100/1000T	48x 10/100/1000T
Uplink	2x GE SFP	4x GE SFP	4x GE SFP
Stacking	-	-	-
Features	L2, IPv6, Cisco CLI	L2, IPv6, Cisco CLI	L2, IPv6, Cisco CLI
PoE	PoE+ (max. 65/125W)	PoE+ (max. 200/370/740W)	-
Power Supply	AC	AC	AC







L2/L2+/L3 Lite Managed 1G/10G Ethernet Switches for ISP/Enterprise

1G Uplink	 TOP!	 TOP!	 TOP!
Typ	ECS4100-12T/12PH	ECS4100-28T/28P	ECS4100-52T/52P
Main ports	8x 10/100/1000T	24x 10/100/1000T	48x 10/100/1000T
Uplink	2x GE Combo/2x GE SFP	2x GE Combo/2x GE SFP	2x GE Combo/2x GE SFP
Stacking	IP	IP	IP
Features	L2/L2+ Cisco-like CLI, IPv6	L2/L2+ Cisco-like CLI, IPv6	L2/L2+ Cisco-like CLI, IPv6
PoE	PoE+ max. 180W	PoE+ max. 190W	PoE+ max. 370W
Power Supply	AC or DC (24/48V)	AC or DC (24/48V)	AC

1G/10G Uplink	 TOP!	 NEW!	 TOP!	 NEW!
Typ	ECS4120-28T/52T	ECS4130-28T Compact Size	ECS4120-28Fv2/ECS4120-28Fv2-I-S Extended operating range -10/+65°C	ECS4530-54CSFP/DC-I Extended operating range 0/+60°C
Main ports	24x/48x 10/100/1000T	24 x 10/100/1000T	20x FE/GE SFP	20 x 1G CSFP plus 4 x Combo (4 x RJ45 / 2 x CSFP)
Uplink	4x 10GE SFP+	4x 10GE SFP+	4x 10GE SFP+ 4x GE Combo	4x 10G SFP+ plus 2x 20G QSFP+
Stacking	IP	IP	IP, HW (28Fv2-I-S)	IP
Features	L2/L2+, Cisco-like CLI, IPv6	L2/L3 Lite, Cisco-like CLI, IPv6	L2/L2+, Cisco-like CLI, IPv6	L2/L3 Lite, Cisco-like CLI, IPv6
PoE	-	-	-	-
Power Supply	AC or DC (24/48V)	AC or DC 48V	AC + DC 48V	AC or DC 48V

L3 Full Managed Gigabit Ethernet Switches

				
Typ	ECS4620-28T/28P/52T/52P	ECS4620-28F	ECS5520-18T	ECS5520-18X
Main ports	24x or 48x 10/100/1000T	22x FE/GE SFP	16x 10G RJ-45	16x 1G/10G SFP+
Uplink	2x 1G/10G SFP+, opt. 2x 10G	2x 1G/10G SFP+, opt. 2x 10G	2x 40G QSFP+ or 8x 10G via Break Out Cable	2x 40G QSFP+ or 8x 10G via Break Out Cable
Stacking	HW	HW	-	-
Features	L3, Cisco-like CLI, Ipv6	L3, Cisco-like CLI, IPv6	L2, L2+ Cisco-like CLI, IPv6	L2, L2+ Cisco-like CLI, IPv6
PoE	PoE+ (max. 410/780W)	-	-	-
Power Supply	AC or DC 48V(28T-DC)	AC or DC 48V	AC or DC 48V	AC or DC 48V

L2 Full Managed 10 Gigabit Ethernet Switches

Autorizovaný distributor pro ČR a SR

PROFcomms s.r.o. nabízí k produktům Edge-Core přidanou hodnotu:

- technická podpora - technici certifikovaní přímo od výrobce
- návrhy sítí a školení

Kontakt

Ing. Petr Dorociak
product & Sales manager
tel.: +420 548 210 406 kl. 264
mobil: +420 736 625 864