

FSP 150-GE100Pro Series

Programmable Carrier Ethernet and IP demarcation

Benefits

- **Universal use**
A unique, comprehensive combination of features for future-proof network demarcation
- **Adtran ConnectGuard™ security**
Securing traditional leased lines without compromising bandwidth or latency.
- **Multilayer technology**
Extending Ethernet demarcation with forwarding, filtering and advanced monitoring capabilities for IP traffic
- **Timing excellence**
Assured, highly precise frequency-, phase-, and time-synchronization featuring SyncE and IEEE 1588 PTP
- **Temperature hardened**
Different construction practice for rack-mount indoor but also fanless outdoor applications
- **Ensemble management and control**
Ensemble Controller with future-proof SDN control and open API

Overview

As complexity increases, network demarcation devices need to continuously extend their capabilities.

Communication service provider need one product family for Ethernet and IP, indoor or outdoor, sophisticated security and highly precise synchronization.

Change is the norm. Today, your business customer wants Ethernet connectivity. Tomorrow, it's IP services. Frequency synchronization is no longer sufficient for your mobile network as time synchronization is mandatory for 4G. Meanwhile, your customers decide that they won't accept unencrypted transmission. The one constant is that requirements keep changing – and at an unprecedented pace. Our FSP 150-GE100Pro series belongs to the successful FSP 150 ProNID family. It enables network operators to offer true multi-service access by combining the demarcation of Carrier Ethernet 2.0 and IP services with a rich set of features in a single device. What's more, there's a range of designs from ultra-compact to rack-mountable devices, all aligned with distinct customer demand. The comprehensive FSP 150-GE100Pro series provides the perfect answer to any demarcation requirement.



Product specifications

	Access capacity (ports)	Network capacity (ports)	Synch.	Encryption	Operating temperature	Power supply	Size	Power consumption (nominal)
¹ GE101Pro	1xGE	1xGE	–	–	0°C to +45°C	External, AC	Ultra compact	6.5W
² GE102Pro(H)	1xGE	2xGE	–	–	0°C to +45°C	Integrated, DC or AC	1 RU (H) full width	15W
³ GE112Pro (m)	2xGE	2xGE	–	–	–40°C to +70°C	External, AC or DC	1 RU (H) compact	19W
⁴ GE112Pro	2xGE	2xGE	–	–	–40°C to +65°C	Integrated, DC or AC	1 RU (H) half width	19W
⁵ GE112Pro (H)	2xGE	2xGE	–	–	–40°C to +65°C	Modular, DC or AC	1 RU (H) full width	21W
⁶ GE114Pro	4xGE	2xGE	–	–	–40°C to +65°C	Integrated, DC or AC	1 RU (H) half width	23W
⁷ GE114Pro (C)	4xGE	2xGE	–	 Connect Guard™	–40°C to +65°C	Integrated, DC or AC	1 RU (H) half width	23W
⁸ GE114Pro (HE)	4xGE	2xGE	–	–	–40°C to +65°C	Modular, DC or AC	1 RU (H) full width	24W
⁹ GE114Pro (SH)	4xGE	2xGE	SyncE, PTP	–	–40°C to +65°C	Modular, DC or AC	1 RU (H) full width	30W
¹⁰ GE114Pro (CSH)	4xGE	2xGE	SyncE, PTP	 Connect Guard™	–40°C to +65°C	Modular, DC or AC	1 RU (H) full width	30W

Access capacity

- One¹ 10/100/1000BaseT or 100/1000BaseX (SFP) port
- One² 10/100/1000BaseT or 100/1000BaseX (SFP) port
- Two³ ports:
 - one dedicated 100/1000BaseX (SFP) port
 - one 10/100/1000BaseT or 100/1000BaseX (SFP) port
- Two^{4,5} / Four^{6–10} 10/100/1000BaseT or 100/1000BaseX (SFP) ports

Network interface

- One¹ 10/100/1000BaseT or 100/1000BaseX (SFP) port
- Two^{2,3} 100/1000BaseX (SFP) ports
- Two^{4–10} 10/100/1000BaseT or 100/1000BaseX (SFP) ports
- One network port can be defined as an additional access port^{2–10}

Network interface redundancy^{2–10}

- IEEE 802.1AX link aggregation – active/standby^{2–10} or load balancing^{3–10}
- ITU-T G.8032 Ethernet ring protection^{3–10}

Synchronization^{9–10}

- ITU-T G.8261 / G.8262 / G.8264 Synchronous Ethernet on all interfaces
- Sync status message support
- IEEE 1588v2 Precision Time Protocol
- ITU-T G.8265.1 and G.8275.1 PTP Telecom Profile
- BITS-in and BITS-out
- BITS sync status messaging
- 1 PPS in/out
- 10MHz

VLAN support

- 4096 VLANs (IEEE 802.1Q customer-tagged) and stacked VLANs (Q-in-Q service provider tagged)
- 2-tag management (push/pop/swap) for c-tag and s-tag

FSP 150-GE100PRO SERIES

- IEEE 802.1ad provider bridging (c-tag, s-tag)
- Ethertype translation
- 8^{1,2} / 32³⁻⁵ / 64⁶⁻¹⁰ Ethernet virtual circuits (EVC)
- 9612 Byte per frame MTU transparency
- EoMPLS encapsulation

Layer 2 traffic management

- Acceptable client frame policy: tagged or untagged
- Service classification based on IEEE 802.1p, 802.1Q and IP-TOS/DSCP
- VLAN tag priority mapping (IEEE 802.1ad PCP encoding)
- MEF-compliant policing (CIR / CBS / EIR / EBS) with three-color marking and eight classes of service
- Port shaping on transmit for both client and network ports
- MEF 10.3 hierarchical policing with token-share envelopes
- DiffServ supporting WFQ/SP mix

Layer 3 traffic management

- L2-L4 access control lists (ACL) for classification
- VRF-lite virtual routing and forwarding supporting IPv4 and IPv6
- BGP and OSPF dynamic routing
- DHCP relay agent
- DCSP remarking
- VRRP, NAT

Operation, administration and maintenance (OAM)

- IEEE 802.3ah EFM-OAM link management
- IEEE 802.1ag connectivity fault management (CFM) with hardware assistance
- ITU-T Y.1731 performance monitoring
- ITU-T Y.1564 service activation testing
- Terminal and facility loopbacks on port- and EVC-level for all interfaces
- Cable diagnostics with benchmarks (electrical interfaces only)
- Embedded RFC 2544 test generator and analyzer (ECPA)
- MEF-compliant Layer 2 control protocol disposition and extensive filter options for Layer 2 packet types
- Link loss forwarding to signal local link and network path failures
- Dying gasp message for power failure alarming (EFM-OAM and SNMP trap option)
- Port mirroring (local and remote)³⁻⁹

Performance monitoring

- RFC 2819 RMON Etherstats on a per-port and per-service basis
- 15-minute and 1-day performance data bins
- IEEE 802.3ah / ITU-T G.8021 PHY level monitoring
- ITU-T Y.1731 single- and dual-ended frame loss measurement²⁻⁹
- Synthetic frame loss and delay measurement for multi-point service monitoring
- TWAMP sender / reflectors for L3 based service assurance
- Multi-CoS monitoring on EVCs scaling up to 32^{1,2} / 64³ / 128⁴⁻¹⁰ simultaneous SOAM flows
- Threshold-setting and threshold-crossing alerts
- Physical parameter monitoring for SFP optics, including TCAs
- Temperature monitoring and thermal alarms

ConnectGuard™ security^{7,10}

- L2 MACsec encryption at line rate on a per-EVC basis
- End-to-end encryption mode with one or two VLAN tags transmitted in the clear
- Robust AES encryption algorithm (AES-128 / AES-256)
- Key distribution based on IEEE 802.1X
- Diffie-Hellmann key exchange process (2048 / 4096 bits)
- Tamper resistant and evident enclosure
- Full interoperability with all FSP 150 ConnectGuard™-enabled products

Low-touch provisioning

- DHCP / BOOTP auto-configuration
- IEEE 802.1x port authentication (supplicant and authenticator)
- Text-based configuration files
- TFTP / SCP for software image upgrade and configuration file copy

Management and security

Local management

- Serial connector (RJ45) using CLI³⁻¹⁰
- Local LAN port (RJ45) using CLI, SNMP and Web GUI interfaces²⁻¹⁰
- USB (Type B Micro) using CLI¹
- USB (Type B Mini) using CLI²
- 3G / LTE / WiFi USB interface

Remote management

- Maintains in-band VLAN and MAC-based management tunnels
- Fully interoperable with other FSP 150 products

Management protocols

- IPv4 and IPv6 DCN protocol stacks, including dual-stack operation and 6-over-4 tunnels
- Telnet, SSH (v1/v2), HTTP/HTTPS, SNMP (v1/v2c/v3)
- NETCONF/YANG, OpenFlow

Secure administration

- Configuration database backup and restore
- System software download via FTP, HTTPS, SFTP or SCP (dual flash banks)
- Remote authentication via RADIUS/TACACS
- SNMPv3 with authentication and encryption
- Access control list (ACL)

IP routing

- DHCP, RIPv2 and static routes, ARP cache access control

System logging

- Alarm log, audit log and security log

Regulatory and standards compliance

- MEF CE 2.0 certified
- IEEE 802.1Q (VLAN), 802.1p (Priority), 802.1ag (CFM), 802.3ah (EFM), 802.1x
- ITU-T Y.1731, G.8010/Y.1306, G.8011.1+2, G.8032³⁻¹⁰
- MEF-6.1, -9, -10.2, -11, -14, -20, -21, -22.1, -23.1, -25, -26.1, -30, -33, -35, -36
- IETF RFC 2544 (Frame Tests), RFC 2863 (IF-MIB), RFC 2865 (RADIUS), RFC 2819 (RMON), RFC 5357 (TWAMP)
- MEF-compliant ITU-T Y.1564 Service Activation Testing
- ETSI 300 132-2, ETS 300-019-2
- Telcordia GR-499, GR-63-CORE, SR-332²⁻¹⁰
- Safety IEC/UL/EN 62368-1, 21CFR1040.10, EN 60825, EN 50371, EN 300-386, EN 50160, IEC 60320/C14
- EMI EN 300-386, GR-1089-CORE, ETS 300-132, FCC Part 15, Class A³⁻¹⁰, Class B^{1,2}, Industry Canada

Environmental

- Dimensions (W x H x D):
 - 113mm x 38mm x 113mm / 4.5" x 1.5" x 4.5"¹
 - 436mm x 44mm x 211mm / 17.1" x 1.7" x 8.3"²
 - 145mm x 34mm x 152mm / 5.7" x 1.3" x 6.0"³
 - 220mm x 44mm x 218mm / 8.7" x 1.75" x 8.6"^{4,6,7}
 - 443mm x 44mm x 208mm / 17.4" x 1.7" x 8.2"⁵
 - 443mm x 44mm x 218mm / 17.4" x 1.7" x 8.6"⁸⁻¹⁰
- Operating temperature:
 - 0°C to +45°C / 32°F to 113°F^{1,2}
 - -40°C to +70°C / -40°F to 158°F (hardened environment)³
 - -40°C to +65°C / -40°F to 149°F⁴⁻¹⁰ (hardened environment)
- Storage temperature: -40°C to +70°C / -40°F to 158°F (GR-63-CORE)
- Humidity: 5 to 95%, BI (non-condensing)
- Power supply:
 - External 110/240VAC, -48 to -72VDC power adapter^{1,3}
 - Fixed, redundant PSUs, 110/240VAC, -36 to 72VDC with over-voltage and over-current protection²
 - Integrated PSU^{4,6,7} / redundant modular hot-swappable PSU^{5,8-10}: 110/240VAC, -48 to -72VDC with over-voltage and over-current protection
- Power consumption:
 - Nominal: 6.5W¹, 12.5W², 19W^{3,4}, 21W⁵, 23W^{6,7}, 24W⁸, 30W^{9,10}
 - Maximum: 10W¹, 15W², 23W^{3,4}, 25W⁵, 28W^{6,7}, 29W⁸, 35W^{9,10}
- Dry-contact environmental alarm inputs⁸

Product legend

- ¹ FSP 150-GEI01Pro
- ² FSP150-GEI02Pro (H)
- ³ FSP 150-GEI12Pro (m)
- ⁴ FSP 150-GEI12Pro
- ⁵ FSP 150-GEI12Pro (H)
- ⁶ FSP 150-GEI14Pro
- ⁷ FSP 150-GEI14Pro (C)
- ⁸ FSP 150-GEI14Pro (HE)
- ⁹ FSP 150-GEI14Pro (SH)
- ¹⁰ FSP 150-GEI14Pro (CSH)



June Copyright © 2023 Adtran, Inc. All rights reserved. Adtran believes the information in this publication to be accurate as of publication date, and is not responsible for error. Specifications subject to change without notice. Adtran and the other trademarks listed at www.adtran.com/trademarks are registered trademarks of Adtran, Inc. or its affiliates in various countries. All other trademarks mentioned in this document are the property of their respective owners.

Adtran warranty duration and entitlements vary by product and geography. For specific warranty information, visit www.adtran.com/warranty.

Adtran products may be subject to U.S. export controls and other trade restrictions. Any export, re-export, or transfer of the products contrary to law is prohibited. For more information regarding exportation of Adtran items (e.g. commodities, technology, software), please visit www.adtran.com/exportlicense.

